



Linear Torque Arms

Consult ASG to request a quote for your specific application.

Linear Positioning Torque Arms

- 260 MM (10 1/4") horizontal stroke
- X-Y and X-Y-Z position sensing available
- I/O for interfacing with control devices
- Two and three encoder models have a position accuracy of 0.2mm horizontally and/or vertically and 0.5° rotationally
- 32 programs available, selectable from the key pad or remotely through the I/O
- Standard "split block" tool holder for 25 to 50mm diameter tools. Optional special tool holders available
- Standard tool balancer provided. Optional balancers available

Model Number	ASG Number	Description
LPTA040-2E	66206	Linear Positioning Torque Arm 40 N.m 2 Encoders
LPTA100-2E	66207	Linear Positioning Torque Arm 100 N.m 2 Encoders
LPTA040-3E	66208	Linear Positioning Torque Arm 40 N.m 3 Encoders
LPTA100-3E	66209	Linear Positioning Torque Arm 100 N.m 3 Encoders



ASG Linear Torque Arms

Linear Torque Arms

- Standard “split block” tool holder for 25 to 50mm diameter tools. Optional special tool holders available
- 260 MM (10 ¼”) horizontal stroke
- Standard tool balancer provided. Optional balancers available
- Suitable for many applications

Model Number	ASG Number	Description
LTA20	66203	Linear Torque Arm 20 N.m
LTA40	66204	Linear Torque Arm 40 N.m
LTA100	66205	Linear Torque Arm 100 N.m



Dimensional Information

