



## Brushless Electric Screwdrivers

- High quality brushless motor guarantees outstanding output torque and durability without maintenance
- Slow Start feature when using the BTL-5A power supply with standard size screwdrivers
- Excellent torque repeatability
- Torque ranges from 0.17 to 15.6 lbf.in
- Internal speed adjustable from 100 to 750 RPM for mini brushless screwdrivers
- Ergonomic design, small and light weight
- Quiet
- Use only recommended power supply



**BTL-05**  
(65650)



**BTL-10**  
(65651)



**BTL-15**  
(65652)



**Recommended Power Supply:**  
**BTL-5A (65710)**



**BTL-02A (65648)**  
**BTL-03A (65649)**



**Recommended 110V**  
**Power Supply:**  
**BTL-2A24 (65708)**

Model Number	ASG Number	Torque Range			Speed RPM	Rated Voltage	Length		Weight		Drive Size
		lbf.in	N.m	kgf.cm			mm	in.	g	lb.	
BTL-02A	65648	0.17 - 1.30	0.02 - 0.15	0.20 - 1.50	100 - 750	24V DC	180	7.1	210	0.46	4 mm
BTL-03A	65649	0.43 - 2.60	0.05 - 0.30	0.50 - 3.00	100 - 750	24V DC	180	7.1	210	0.46	4 mm
BTL-05	65650	0.43 - 4.80	0.05 - 0.55	0.5 - 5.5	1000	30V DC	220	8.7	345	0.76	1/4" Hex
BTL-10	65651	0.90 - 10.4	0.10 - 1.2	1.0 - 12.0	1000	30V DC	220	8.7	345	0.76	1/4" Hex
BTL-15	65652	1.7 - 15.6	0.2 - 1.8	2.0 - 18.0	850	30V DC	220	8.7	345	0.76	1/4" Hex

Quality Certified ISO 9001:2008

ASG, Division of Jergens, Inc.  
Jergens Way, 15700 S. Waterloo Road  
Cleveland, OH 44110-3898

Toll Free: (888) 486-6163 | Fax: (216) 481-4519

Email: [asginfo@asg-jergens.com](mailto:asginfo@asg-jergens.com) | [www.asg-jergens.com](http://www.asg-jergens.com)

