



Screwdrivers with Reverse Capability

- Ergonomic reverse lever tool with forward pistol grip
- Reversibility lever can be positioned on the right or left of the start button
- Light weight, well balanced
- Anti-slip insulating grip
- Available in the 15C...R and 26C...R

Model/ASG Number	Ported for Error-Proofing Part Number/ Model Number	Torque Range		Free Speed	Weight	Length	Diameter	Height	Air Consumption	Drive Size	Min Hose I.D.	Noise Level
		lbf.in	N.m	RPM	lb.	in.	ø in.	in.	CFM		in.	± 2dBA
15C2APA-2200-R	15C2APA-2200-R-2CS	5.31 - 19.47	0.6 - 2.2	2200	1.65	7.32	1.46	6.10	12.7	1/4 Hex	3/16	71
15C3APA-1400-R	15C3APA-1400-R-2CS	3.54 - 30.98	0.4 - 3.5	1400	1.69	7.32	1.46	6.10	12.7	1/4 Hex	3/16	71
15C4APA-950-R	15C4APA-950-R-2CS	3.54 - 39.83	0.4 - 4.5	950	1.69	7.32	1.46	6.10	12.7	1/4 Hex	3/16	71
15C5APA-650R	15C5APA-650-R-2CS	3.54 - 44.25	0.4 - 5	650	1.69	7.32	1.46	6.10	12.7	1/4 Hex	3/16	71
26C4APA-2000-R	26C4APA-2000-R-2CS	3.54 - 35.4	0.4 - 4	2000	2.05	8.14	1.46	6.10	14.8	1/4 Hex	5/16	73
26C5APA-1350-R	26C5APA-1350-R-2CS	3.54 - 44.25	0.4 - 5	1300	2.05	8.14	1.46	6.10	14.8	1/4 Hex	5/16	73
26C8APA-1000-R	26C8APA-1000-R-2CS	30.98 - 70.8	3.5 - 8	1000	2.33	9.21	1.46	6.10	14.8	1/4 Hex	5/16	73
26C10APA-800-R	26C10APA-800-R-2CS	30.98 - 84.08	3.5 - 9.5	800	2.33	9.21	1.46	6.10	14.8	1/4 Hex	5/16	73
26C12APA-400-R	26C12APA-400-R-2CS	30.98 - 106.2	3.5 - 12	400	2.33	9.21	1.46	6.10	14.8	1/4 Hex	5/16	73